



LITHIUM SALTS

Lithium Salts of America (Lith) is primary in lithium and is involved with the supply chain all the way from the hard rock mining of lithium bearing ores such as spodumene and lepidolite to the down stream chemistries of lithium silicate, specialty binders and other specialties such as lithium chloride, lithium fluoride and lithium acetate. For more information about our unique position on lithium chemistries and product offerings visit Lithium Salts of America (Lith) a division of ASG Chemie www.lithiumsalts.com

LITHIUM SILICATES

 $\text{Li}_2\text{O}_3\text{Si}$ **LITHIUM SILICATE (LS)45**

Solids 23%

Lithium Silicate (LS)45 (Solids 23%) is an aqueous polysilicate solution with a molar ratio of 4.5 (ranging 4.35-5.0) that has a high concentration of lithium produced with Lithium Hydroxide. The reactive silicate forms a stable, high ratio, low viscosity solution that results in lower levels of water in coatings and can dramatically improve film formation, water resistance, abrasion, hardness and bonding properties for many applications, including concrete surface treatments, specialty paints and coatings. Adhesion: Addition of Lithium Silicate to Sodium or Potassium Silicates improves the adhesion to a wide variety of substrates.

 $\text{Li}_2\text{O}_3\text{Si}$ **LITHIUM SILICATE (LS)45 HS**

Solids 28%

Lithium Silicate (LS)45 HS (Solids 28%) is a high solids aqueous polysilicate solution with a molar ratio of 4.5 (4.2-4.8) allows for improved interaction and compounding when used as a reactive binder and/or hardener in coatings, treatments, and sealers. The reactive silicate has a higher concentration of lithium and is preferred to sodium and/or potassium silicates for many applications, including concrete surface treatments, specialty paints and coatings. Especially suitable for high performance zinc coatings for marine and industrial applications in which high pigment loading and water and wear resistance are desired.

 $\text{Li}_2\text{O} \cdot \text{K}_2\text{O} \cdot \text{SiO}_2$ **LITHIUM POTASSIUM SILICATE (LPS)39**

Solids 29%

Lithium Potassium Silicate (LPS)39 (Solids 29%) is an aqueous polysilicate hybrid blended solution with a molar ratio of 3.9 (ranging 3.8-4.0). Ideal for many applications including; concrete surface treatments, specialty paints and coatings, welding rod binders, refractory materials, ceramics and glazes.

LITHIUM METASILICATE

 Li_2SiO_3 **LITHIUM METASILICATE**

Lithium Metasilicate - used in glass system, molten salt system and high temperature ceramic glazes, also as a binder, mainly for inorganic zinc-rich coatings and advanced electrodes.

LITHIUM HYDROXIDE

 $\text{LiOH} \cdot \text{H}_2\text{O}$ **LITHIUM HYDROXIDE, Monohydrate**

Lithium Hydroxide, Monohydrate is used in a variety of applications including producing lithium complex grease, carbon dioxide absorber and as a fluxing agent in inorganic pigments. Available grades include, technical, battery as well as of-spec material.

 $\text{LiOH} \cdot \text{H}_2\text{O}$ **LITHIUM HYDROXIDE, Monohydrate**

Battery Grade

Lithium Hydroxide, Monohydrate (Battery Grade) - high purity variant of lithium hydroxide monohydrate is suitable for use in cathode materials to produce lithium ion batteries, as well as other fine chemical applications where low impurities is of importance.

 $\text{LiOH} \cdot \text{H}_2\text{O}$ **LITHIUM HYDROXIDE, Anhydrous**

Lithium Hydroxide, Anhydrous is a less easily stored and transported form of lithium hydroxide, however it finds some unique applications such as in the production of lithium stearate as well as heat transfer medium for storage battery electrolyte.

LITHIUM CARBONATE

Li₂CO₃**LITHIUM CARBONATE**

Ultrafine Grade

Lithium Carbonate (Ultrafine Grade) is an odourless, white free flowing powder with a median particle size is 6-10 microns. It is the finest particle size and the highest reactivity of the lithium carbonate grades available with low impurities and a narrow particle size distribution. The smaller particle size results in a higher effective surface area and thus is more reactive. That has a wide range of applications.

Li₂CO₃**LITHIUM CARBONATE**

Superfine Grade

Lithium Carbonate (Superfine Grade) is an odourless, white free flowing powder with a median particle size is < 40 microns. It is a high concentration lithium carbonate with low impurities and a narrow particle size distribution. The smaller particle size results in a higher effective surface area and thus is more reactive offering more predicable rates of reactions That has a wide range of applications.

Li₂CO₃**LITHIUM CARBONATE**

Technical Grade

Lithium Carbonate (Technical Grade) offers a much coarser particle size than the ultrafine or superfine grade, the technical grade is better suited for frits and glazes, as well as for producing other down stream lithium chemistries.

Li₂CO₃**LITHIUM CARBONATE**

Battery Grade

Lithium Carbonate (Battery Grade) is a high purity 99.5% fine white powder material recommended for use in Li-ion battery precursors to portable electronics applications. Average particle granularity of < 6 microns.

LITHIUM SULFATE

Li₂SO₄**LITHIUM SULPHATE**

Lithium Sulphate is used across a range of technical industries. It accelerates setting time in high alumina cements, is used as an additive in special glasses and photographic developing solutions, and is a catalyst in various polymer reactions. It is also the main component of electrolytes in large-scale battery formulations for grid storage applications.

Available Grades: Anhydrous Technical, Monohydrate Industrial Grade, Monohydrate Technical, Monohydrate ACS and 20% Solution is a clear aqueous solution.

LITHIUM CHLORIDE

LiCl

LITHIUM CHLORIDE, Anhydrous

98%

Lithium Chloride, Anhydrous (98%) is used in the production of lithium metal, as well as a brazing flux in the automotive industry. Lithium chloride is also used in some nitche applications such as it's use as a tracer in water treatment plants.

LiCl

LITHIUM CHLORIDE

40% Solution

Lithium Chloride (40% Solution) in water is a ready to use aqueous solution, lithium chloride solution can be used in water treatment as well as a feedstock for making lithium metal and other lithium chemistries. Other dilutions available upon request.

LITHIUM NITRATE

LiNO₃**LITHIUM NITRATE** Admixture

30% Solution

Lithium Nitrate, Admixture (30% Solution) is a concrete admixture designed for the prevention and control of alkali-silica reactivity. A cost effective method for improving durability, as well as allowing safe utilization of locally available aggregates and cement.

LiNO₃**LITHIUM NITRATE ASR MITIGATION** Treatment

30% Solution

Lithium Nitrate ASR Mitigation, Treatment (30% Solution) is a formulated proprietary solution which is used as a topically applied treatment to help in the remediation of concrete structures and infrastructures presently affected by ASR as a cost-effective way to impregnate concrete with lithium ions to help control cracking, pop-outs and costly repairs caused by ASR.

LITHIUM BROMIDE

LiBr

LITHIUM BROMIDE

55% Solution

Lithium Bromide (55% Solution) is a high concentration aqueous lithium bromide suitable for use as a reagent, as a coolant in nuclear towers as well as in medical applications.

LiBr

LITHIUM BROMIDE, Anhydrous

98%

Lithium Bromide, Anhydrous (98%) is extremely hygroscopic by nature, lithium bromide anhydrous is well suited as a desiccant in air conditioning systems, as well as a humectant and fungicide in medicinal applications.

LITHIUM FLUORIDE

LiF

LITHIUM FLUORIDE, Powder

Lithium Fluoride, Powder is most widely used as a flux in the production of ceramics, such as enamels, glasses and glazes. Similarly it is also used in brazing and welding flux and molten salt chemistry in metallurgy.

LITHIUM ACETATE

LiOAc

LITHIUM ACETATE, Anhydrous

Lithium Acetate, Anhydrous is a white granular powder that is freely soluble in water and short chain alcohols. Anhydrous lithium acetate is obtained by heating commercial lithium acetate till the melting point of anhydrous salt, and then cooling it very slowly. Mainstream applications include: Buffer for ion exchange chromatography in the production of industrial polymers and resins; Precursor for lithium ceramic cathode materials in the manufacture of textiles and lubricant greases; Key component of solid polymer blend electrolytes; PVC stabilizer, and as an anti static additive.

LiOAc

LITHIUM ACETATE

29% w/w Solution

Lithium Acetate (29% w/w Solution) is used as an additive to industrial clearers for neutralizing for carbonated floors, as a highly effective de-icer that is non-corrosive to concrete and stabilizing additive for cleaners to help reduce alkalis as well as a catalyst for oxidation and hydroformylation of organic compounds for their deprotonation and dehydration.

LITHIUM MINERALS

LiAl(SiO₃)₂**SPODUMENE**

Spodumene is a pyroxene mineral and a source of lithia. It is used in glasses, ceramics, porcelain enamels, white wares and glazes due to its powerful fluxing properties. It has low thermal expansion, reduces the melt viscosity, melting temperature and contributes to brilliancy and strength of the glass.

LiAlSi₄O₁₀**PETALITE**

Petalite, also known as castorite, is a lithium aluminum phyllosilicate mineral. It is used in ceramics, glass and enamels. The addition of petalite improves strength, density, acid resistance, heat resistance and gloss. It reduces melt viscosity, melting temperature and thermal expansion, and

promotes melt homogenization.

SPECIALTY LITHIUM CHEMISTRIES

LithMelt™ Anti-icer / De-icer

LithMelt™ is a proprietary, fully formulated deicing composition. The composition includes a potassium or sodium salt of a carboxylic acid and a lithium salt of a carboxylic acid or lithium nitrate, wherein the molar ratio of lithium to potassium or lithium to sodium is from 10 percent to 80 percent.

Micro-Dur™ Hybrid Polymer Dispersion

Micro-Dur™ Hybrid Polymer Dispersion is a specialty organic-inorganic hybrid micro-dispersion composed of nano-silica, lithium silicate and silicon in a resin matrix. The specifically engineered composition and self-cross-linking mechanism provides superior hardness, durability, adhesion, chemical and stain resistance to waterborne clear topcoats, varnishes, and stains.

Keep informed of the latest news, product availability, specifications and information pertaining to R&D papers and technical insights and so much more.

www.lithiumsalts.com

Performance Lithium and Specialty Chemicals



Lithium Salts of America www.lithiumsalts.com

Lithium Salts of America is a Division of ASG Chemical Holdings, LLC (ASG Chemie) • www.lithiumsalts.com
2603 NW 13th St. #231 Gainesville, FL 32609 • Main : 352.432.1481 • Fax : 352.430.7442 • Toll Free : 1.833.LITHUSA (548.4872)

©2024 Lithium Salts of America (LITH). All Rights Reserved. Lith logo and ASG Chemie are trademarks of ASG Chemical Holdings, LLC.